



Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

Product # 317331 – 15 gal
310473 – 50 gal

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name: Flexible FAST Adhesive Part B

Synonyms: Polyol Blend.

Chemical Family: Polyol Blend

Product Use: Commercial Roofing Adhesive

Restrictions on Use: Professional use only

Manufacturer Information

Carlisle SynTec
1285 Ritner Highway
Carlisle, PA 17013
USA
Phone: +1-800-479-6832
Emergency Phone #: +1-800-424-9300 (CHEMTREC)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

None needed according to classification criteria

GHS Label Elements

Symbol(s)

None needed according to classification criteria

Signal Word

None needed according to classification criteria

Hazard Statement(s)

None needed according to classification criteria

Precautionary Statement(s)

Prevention

None needed according to classification criteria

Response

None needed according to classification criteria

Storage

None needed according to classification criteria

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

Product # 317331 – 15 gal
310473 – 50 gal

Other Hazards

No additional information available.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
25265-71-8	Dipropylene glycol	5-10
13674-84-5	2-Propanol, 1-chloro-, phosphate (3:1)	10-20
280-57-9	1,4-Diazabicyclo[2.2.2]octane	0.1-1
108-01-0	2-(Dimethylamino)ethanol	0.1-1

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

IF exposed or concerned: Get medical advice/attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

Skin

Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention.

Eyes

Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

No information on significant adverse effects.

Delayed

No information on significant adverse effects.

Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

Product # 317331 – 15 gal
310473 – 50 gal

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

regular dry chemical, carbon dioxide, water, regular foam

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

Closed containers may rupture violently when heated.

Hazardous Combustion Products

Oxides of carbon, oxides of phosphorus, hydrogen halides

Special Protective Equipment and Precautions for Firefighters

Wear self-contained breathing apparatus with a full facepiece and protective clothing.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Do not touch or walk through spilled material. Stop leak if possible without personal risk. Small spills: Absorb with earth, sand or other non-combustible material and transfer to container. Large spills: Dike for later disposal. Eliminate all sources of ignition. Do not flush into sanitary sewer systems, drains or surface water.

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Use only in well ventilated areas. Wear protective gloves/clothing and eye/face protection. Wash contaminated clothing before reuse.

Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

**Product # 317331 – 15 gal
310473 – 50 gal**

Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria

Store between 65°F-85°F (18°C-30°C). Store in a dry place. Keep away from incompatible materials.

Incompatible Materials

Strong oxidizing materials, isocyanates, strong acids, strong bases

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

ACGIH, NIOSH, EU, OSHA (US) and Mexico have not developed exposure limits for any of this product's components

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear chemical resistant clothing and rubber boots when potential for contact with the material exists. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Respiratory Protection

In case of inadequate ventilation wear respiratory protection.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	blue liquid	Physical State	liquid
Odor	musty, amine	Color	blue
Odor Threshold	Not available	pH	9.2
Melting Point	Not available	Boiling Point	>100°C
Freezing point	Not available	Evaporation Rate	slower than ether
Boiling Point Range	Not available	Flammability (solid, gas)	Not available

Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

**Product # 317331 – 15 gal
310473 – 50 gal**

Autoignition	Not available	Flash Point	>201°F [(CC)]
Lower Explosive Limit	Not available	Decomposition	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	>1	Specific Gravity (water=1)	1.1058
Water Solubility	soluble	Partition coefficient: n-octanol/water	Not available
Viscosity	250 cps	Solubility (Other)	Not available
Density	9.23 lb/gal at @ 25°C	Physical Form	liquid
VOC	0 g/l		

Other Information

No additional information available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Prolonged heating above 160°C or storage below 5°C. Avoid heat, flames, sparks and other sources of ignition.

Incompatible Materials

Strong acids, strong bases, strong oxidizing materials, isocyanates

Hazardous decomposition products

Oxides of hydrogen, oxides of phosphorus, hydrogen halides

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

Vapor or mist may cause respiratory tract irritation.

Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

**Product # 317331 – 15 gal
310473 – 50 gal**

Skin Contact

May cause mild skin irritation.

Eye Contact

May cause mild eye irritation.

Ingestion

May cause gastrointestinal disturbances, nausea, vomiting, and diarrhea.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Dipropylene glycol (25265-71-8)

Oral LD50 Rat 14800 mg/kg

Dermal LD50 Rabbit >5000 mg/kg

2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)

Oral LD50 Rat 630 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Inhalation LC50 Rat >7 mg/L 4 h

1,4-Diazabicyclo[2.2.2]octane (280-57-9)

Oral LD50 Rat 1700 mg/kg

Dermal LD50 Rabbit 3200 mg/kg

2-(Dimethylamino)ethanol (108-01-0)

Oral LD50 Rat 1803 mg/kg

Dermal LD50 Rabbit 1220 mg/kg

Inhalation LC50 Rat 1641 ppm 4 h

Water (7732-18-5)

Oral LD50 Rat >90 mL/kg

Immediate Effects

No information on significant adverse effects.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

May cause respiratory tract irritation, skin irritation, and eye irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.



Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

Product # 317331 – 15 gal
310473 – 50 gal

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

Germ Cell Mutagenicity

No information available for the product.

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

No information available for the product.

Medical Conditions Aggravated by Exposure

None reported.

Additional Data

No additional information available.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Avoid release to the environment.

Component Analysis - Aquatic Toxicity

2-Propanol, 1-chloro-, phosphate (3:1)	13674-84-5
Fish:	LC50 96 h Brachydanio rerio 56.2 mg/L [static]; LC50 96 h Pimephales promelas 98 mg/L [static]; LC50 96 h Poecilia reticulata 30 mg/L [static]
Algae:	EC50 72 h Desmodesmus subspicatus 45 mg/L IUCLID; EC50 96 h Pseudokirchneriella subcapitata 4 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 63 mg/L IUCLID
1,4-Diazabicyclo[2.2.2]octane	280-57-9
Fish:	LC50 96 h Pimephales promelas 1510 - 1980 mg/L [flow-through]



Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

Product # 317331 – 15 gal
310473 – 50 gal

2-(Dimethylamino)ethanol	108-01-0
Fish:	LC50 96 h Pimephales promelas 81 mg/L [static]
Algae:	EC50 72 h Desmodesmus subspicatus 35 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 98.77 mg/L IUCLID

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Bioconcentration

No information available for the product.

Other Toxicity

No additional information available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

UN/NA #: Not regulated.

IATA Information:

No Classification assigned.

TDG Information:

UN#: Not regulated.

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations



Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

**Product # 317331 – 15 gal
310473 – 50 gal**

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: No Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Dipropylene glycol	25265-71-8	No	No	No	No	Yes
2-(Dimethylamino)ethanol	108-01-0	No	Yes	No	Yes	Yes

Not listed under California Proposition 65

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on SDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

1,4-Diazabicyclo[2.2.2]octane	280-57-9
	1 %

WHMIS Classification

D2A, D2B.

Component Analysis - Inventory

Oxirane, methyl-, polymer with oxirane (9003-11-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Dipropylene glycol (25265-71-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

**Product # 317331 – 15 gal
310473 – 50 gal**

Siloxanes and Silicones, dimethyl, 3-hydroxypropyl methyl, ethoxylated propoxylated (68937-55-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Oxirane, methyl-, polymer with oxirane, mono-2-propenyl ether (9041-33-2)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

1,4-Diazabicyclo[2.2.2]octane (280-57-9)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

2-(Dimethylamino)ethanol (108-01-0)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Water (7732-18-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 2 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Revision Date: August 10, 2021

Revision Note: General Update



Safety Data Sheet

Material Name: Flexible FAST Adhesive Part B

Product # 317331 – 15 gal
310473 – 50 gal

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.