

GAF Safety Data Sheet SDS # 1064

SDS Date: February 2016

SECTION 1: PRODUCT AND COMPANY INFORMATION

United Coatings[™] Roof Mate Spray Grade Flashing **PRODUCT NAME:**

TRADE NAME: N/A

CHEMICAL NAME / SYNONYM:

N/A

N/A **CHEMICAL FAMILY:**

GAF MANUFACTURER:

> ADDRESS: 1 Campus Drive, Parsippany, NJ 07054

24-HOUR EMERGENCY

PHONE (CHEMTREC): 800 - 424 - 9300

800 - 766 - 3411**INFORMATION ONLY:**

PREPARED BY: Corporate EHS

APPROVED BY: Corporate EHS

SECTION 2: HAZARDS IDENTIFICATION

NFPA and HMIS RATINGS:

	NFPA Hazard Rating		HMIS Hazard Rating
Health	2	Health	2
Flammable	0	Flammable	0
Reactive	0	Reactive	0
Special Hazards	-	Personal Protection	X

GHS LABEL ELEMENTS:

Target Organ (RE) - Category 1 Target Organ (SE) - Category 2 **GHS CLASSIFICATION:**

Eye Irritant - Category 2A Eye Damage - Category 1 Skin Irritant - Category 2 Skin Corrosive - Category 1B Skin Sensitizer - Category 1
Acute Toxicity - Category 4
Mutagenicity - Category 1B
Carcinogenicity - Category 2

Hazardous to the Aquatic Environment (Chronic) - Category 1 Hazardous to the Aquatic Environment (Acute) - Category 1

GHS PICTOGRAMS:







SIGNAL WORD: Warning

HAZARD May cause damage to organs through prolonged or repeated exposure

STATEMENTS: Causes skin irritation

Causes serious eye irritation or damage

Harmful if inhaled Harmful if swallowed

May cause an allergic skin reaction

Repeated exposure may cause skin dryness and cracking

May cause genetic defects Suspected of causing cancer May cause respiratory irritation

Suspecting of damaging fertility or the unborn child Very Toxic to aquatic life with long lasting effects

ADDITONAL HAZARD IDENTIFICATION INFORMATION:

PRIMARY ROUTE OF EXPOSURE: Skin Absorption, Inhalation, and Ingestion

SIGNS & SYMPTOMS OF EXPOSURE

EYES: Exposure to vapors may cause conjunctivitis or eye irritation.

SKIN: Slight irritation of the skin. Prolonged contact can cause reddening

of the skin.

INGESTION: If patient is awake, induce vomiting.

INHALATION: Vapors or mists can cause mental sluggishness, irritation of nasal

passages, throat and lungs. Can cause headaches.

ACUTE HEALTH HAZARDS: Excessive exposure can cause pulmonary edema.

CHRONIC HEALTH HAZARDS: None Known

CARCINOGENICITY: IARC has determined that occupational exposure to Titanium

Dioxide is possibly carcinogenic to humans (Group 2B). IARC concluded lung tumors were observed in rats following high dose exposure by inhalation and in female rats exposed by intra-tracheal instillation. Other studies have shown no tumors in rats following inhalation exposure and no tumors in mice or rats following oral

exposure.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

			OCCUPATIONAL EXPOSURE LIMITS			
CHEMICAL NAME	CAS#	% (BY WT)	OSHA	ACGIH	OTHER	
Calcium Carbonate (Limestone)	1317-65-3	35 - 45	5 mg/m3 - Resp. 15 mg/m3 - Total	NE	REL: 5 mg/m3 - Resp. 10 mg/m3 - Total	
Titanium Dioxide	13463-67-7	2 - 10	10 mg/m3	10 mg/m3 - Total	NE	
Zinc Oxide	1314-13-2	2 - 10	5 mg/m3 - Resp. 15 mg/m3 - Total	2 mg/m3 Respirable	REL: 5 mg/m3 - Dust	
Ammonium Hydroxide	1336-21-6	0 – 2	NE	NE	NE	
Non-Hazardous Ingredients	N/A	50 - 60	NE	NE	NE	

NE = Not Established

SECTION 4: FIRST AID MEASRURES

FIRST AID PROCEDURES

EYES: Flush eyes with water for 15 minutes. If irritation or reddening persists,

call physician.

SKIN: Wash with soap and water.

INHALATION: Move the individual to an area with fresh air or provide oxygen

immediately, call physician.

INGESTION: Call physician immediately.

NOTES TO PHYSICIANS OR

FIRST AID PROVIDERS:

Excessive exposure can cause pulmonary edema.

SECTION 5: FIRE FIGHTING PROCEDURES

SUITABLE EXTINGUISHING MEDIA: Water spray, CO₂, dry chemical or foam for the dry film.

HAZARDOUS COMBUSTION PRODUCTS: N/A

RECOMMENDED FIRE FIGHTING

PROCEDURES:

Use self-contained breathing apparatus and protective

clothing.

UNUSUAL FIRE & EXPLOSION

HAZARDS:

N/A

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Dam up area to prevent spreading of material. Provide ventilation

in closed areas. Dry up the compound using an absorbent

material.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Store in a well ventilated area at temperatures between 50 - 80° F.

OTHER PRECAUTIONS: Protect from freezing.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS / Provide

VENTILATION:

Provide sufficient mechanical ventilation to maintain exposure

below exposure limits.

RESPIRATORY PROTECTION: Use NIOSH approved organic vapor cartridge type respirator if

there is potential to exceed exposure limit(s). Observe OSHA

regulations for respiratory use (29 CFR 1910.134).

EYE PROTECTION: Splash Goggles.

SKIN PROTECTION: Wear appropriate impermeable gloves to prevent skin contact.

OTHER PROTECTIVE EQUIPMENT: N/A

WORK HYGIENIC PRACTICES: Wash exposed skin prior to eating, drinking, or smoking and at the

end of each shift.

EXPOSURE GUIDELINES: N/A

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR:	Heavy white liquid with ammonia odor.				
FLASH POINT:	>240° F	LOWER EXPLOSIVE LIMIT:	No Data		
METHOD USED:	TCC	UPPER EXPLOSIVE LIMIT:	No Data		
EVAPORATION RATE:	1.0	BOILING POINT:	212° F		
pH (undiluted product):	No Data	MELTING POINT:	No Data		
SOLUBILITY IN WATER:	Soluble	SPECIFIC GRAVITY:	1.44		
VAPOR DENSITY:	No Data	PERCENT VOLATILE:	No Data		
VAPOR PRESSURE:	No Data	MOLECULAR WEIGHT:	No Data		
VOC WITH WATER (LBS/GAL):	.33	WITHOUT WATER (LBS/GAL):	No Data		

SECTION 10: STABILITY AND REACTIVIT	Υ			
THERMAL STABILITY:	STABLE X	UNSTABLE		
CONDITIONS TO AVOID (STABILITY):	N/A			
INCOMPATIBILITY (MATERIAL TO AVOID):	N/A			
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:	Carbon monoxide or carbon dioxide.			
HAZARDOUS POLYMERIZATION:	Will not occur.			
SECTION 11: TOXICOLOGICAL INFORMA	ATION			
TOXICOLOGICAL INFORMATION: No information available.				
SECTION 12: ECOLOGICAL INFORMATION	ON			
ECOLOGICAL INFORMATION: No i	information available.			

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: This product, as supplied, is not regulated as a hazardous waste by the

U.S. Environmental Protection Agency (EPA) under Resource

Conservation and Recovery Act (RCRA) regulations. Comply with state

and local regulations for disposal

RCRA HAZARD CLASS: N/A

SECTION 14: TRANSPORTATION INFORMATION

U.S. DOT TRANSPORTATION

PROPER SHIPPING NAME: This product is not classified as a hazardous

liquid for transport.

HAZARD CLASS: N/A

ID NUMBER: N/A

PACKING GROUP: N/A

LABEL STATEMENT: N/A

OTHER: N/A

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA: This product and its components are listed on the TSCA 8(b)

inventory.

CERCLA: N/A

SARA

311/312 HAZARD CATEGORIES: N/A

313 REPORTABLE INGREDIENTS: N/A

CALIFORNIA PROPOSITION 65: N/A

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS#	CA	MA	MN	NJ	PA	RI
Calcium Carbonate (Limestone)	1317-65-3	No	No	Yes	No	Yes	Yes
Titanium Dioxide	13463-67-7	No	No	Yes	Yes	Yes	Yes
Zinc Oxide	1314-13-2	Yes	No	Yes	Yes	Yes	Yes

SECTION 16: OTHER INFORMATION

ADDITIONAL COMMENTS: N/A

DATE OF PREVIOUS SDS: February 2016

CHANGES SINCE PREVIOUS SDS: Name change from Topcoat Flashing – Spray Grade to United

Coatings Roof Mate Spray Grade Flashing.

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.