

## TRI-BUILT® 800 Tile Cement

### SECTION 1: PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME:	TRI-BUILT® 800 Tile Cement	DISTRIBUTED BY:	Beacon Sales Acquisition, Inc.
PRODUCT NUMBER:	TB-8005	ADDRESS:	505 Huntmar Park Drive, Suite 300 Herndon, VA 20170
CATEGORY:	Mixture	PHONE:	571-323-3939
PRODUCT USE:	Repair cracks, seams and holes in roofing materials	INTERNET:	www.becn.com
MANUFACTURER:	APOC		
ADDRESS:	4161 E. 7th Avenue Tampa, FL 33605		
PHONE:	813-248-2101		
EMERGENCY PHONE:	CHEMTREC: 1-800-424-9300 Outside USA and Canada: +703-527-3887		
EFFECTIVE DATE:	7/9/2018		

### Section 2 - Hazards Identification

#### GHS HAZARDS AND PRECAUTIONS

##### SIGNAL WORD: WARNING!

*Flammable liquid (paste) and Vapor. Contains Combustible Petroleum Distillates. Harmful or Fatal if swallowed. Keep away from heat, sparks, and open flame. Avoid prolonged breathing of vapor and use only in adequate ventilation. Repeated and prolonged overexposure to solvent vapor may cause brain and nervous system damage, respiratory tract irritation, dizziness, or loss of consciousness. May cause skin and eye irritation.*

<b>Prevention</b>	Avoid breathing dust, fume, gas, mist, vapours and/or spray. Do not handle until all safety precautions have been read and understood. Keep away from flames and hot surfaces. - No smoking. Use personal protective equipment as required. Keep out of reach of children.
<b>Response</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
<b>Storage/Disposal</b>	Store in a closed container. Store in a well-ventilated place. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.



<b>Physical Form</b>	- Liquid(PASTE)
<b>Color</b>	- Black
<b>Odor</b>	- Petroleum solvent odor.
<b>Flash Point</b>	- 105°F
<b>OSHA HCS 2012</b>	- Flammable Liquids - Category 3, Skin Corrosion/Irritation - Category 2, Serious Eye Damage, Eye Irritation - Category 2A, Carcinogenicity - Category 1A
<b>WHMIS</b>	- Class B - Flammable and Combustible Materials - Division 3, Class D - Poisonous and

## TRI-BUILT® 800 Tile Cement

Infectious Materials - Division 2 - Subdivision A



- GHS**
- Flammable Liquids - Category 3, Skin Corrosion/Irritation - Category 2, Serious Eye Damage, Eye Irritation - Category 2A, Carcinogenicity - Category 1A
- Route Of Entry**
- Inhalation, Skin, Eye, Ingestion/Oral
- Medical Conditions Aggravated by Exposure**
- Lungs/Respiratory System,
- Potential Health Effects**
- Inhalation**
- Acute (Immediate)**
- May cause irritation. Excessive breathing of high vapor concentration can cause possible unconsciousness and even asphyxiation.
- Chronic (Delayed)**
- Refer to other information found in Section 11-Toxicology.
- Skin**
- Acute (Immediate)**
- May cause irritation.
- Chronic (Delayed)**
- Repeated and prolonged exposure to the skin may cause dermatitis.
- Eye**
- Acute (Immediate)**
- May cause burning and redness or swelling of the eyes.
- Chronic (Delayed)**
- Repeated and prolonged exposure may cause irritation.
- Ingestion**
- Acute (Immediate)**
- May be harmful or fatal if swallowed. May cause gastrointestinal disturbances including diarrhea, nausea, and vomiting.
- Chronic (Delayed)**
- Repeated and prolonged exposure may be harmful.
- Carcinogenic Effects**
- This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 - Toxicological Information for more details.

Carcinogenic Effects			
	CAS	IARC	NTP
Asphalt	8052-42-4	Group 2B-Possible Carcinogen	Under Consideration

See Section 12 for Ecological Information.

### Section 3 - Composition/Information on Ingredients

Hazardous Components						
Chemical Name	CAS	%(wt)	UN;EINECS	LD50/LC50	Classifications According to Regulation/Directive	Other
Asphalt	8052-42-4	40% TO 50%	NA1999, 232-490-9	Ingestion/Oral-Rat LD50 · >5000 mg/kgInhalation-Rat LC50 · >94.4 mg/m <sup>3</sup>	<b>WHMIS:</b> Other Toxic Effects - D2A <b>UN GHS:</b> Carc. 2; Eye Irrit. 2A; Skin Irrit. 2 <b>EU DSD/DPD:</b>	NDA
Mineral Spirits	8052-41-3	15% TO 20%	232-489-3		<b>EU DSD/DPD:</b> Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65	NDA
Kaolin	1332-58-7	10% TO 20%			NDA	NDA
Cellulose	9004-34-6	2% TO 10%	232-674-9	Ingestion/Oral-Rat LD50 · >5 g/kgInhalation-Rat LC50 · >5800 mg/m <sup>3</sup> 4 Hour(s)	<b>WHMIS:</b> Other Toxic Effects - D2B <b>UN GHS:</b> Eye Irrit. 2A; Skin Irrit. 2 <b>EU DSD/DPD:</b>	NDA

## TRI-BUILT® 800 Tile Cement

Hazardous Components						
Chemical Name	CAS	%(wt)	UN;EINECS	LD50/LC50	Classifications According to Regulation/Directive	Other
1,2,4-Trimethylbenzene	95-63-6	< 1%	202-436-9	Ingestion/Oral-Rat LD50 · 5 g/kg Inhalation-Rat LC50 · 18000 mg/m <sup>3</sup> 4 Hour(s)	<b>UN GHS:</b> Acute Tox. 4 (Inhalation); Aquatic Chronic 2; Flam. Liq. 3; Eye Irrit. 2A; Skin Irrit. 2; STOT RE 2; STOT SE 2 <b>EU DSD/DPD:</b> R10Xn; R20Xi; R36/37/38N; R51 R53	NDA
Benzene, 1,3,5-trimethyl	108-67-8	< 1%	UN2325, 203-604-4		<b>EU DSD/DPD:</b> R10 Xi; R37 N; R51 R53	NDA
Non-Hazardous Components						
Chemical Name	CAS	%(wt)	UN;EINECS	LD50/LC50	Classifications According to Regulation/Directive	Other
Water	7732-18-5	2% TO 10%	231-791-2	Ingestion/Oral-Rat LD50 · >90 mL/kg	NDA	NDA

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

See Section 11 for Toxicological Information.

### Section 4 - First Aid Measures

- Inhalation**
  - Move victim to fresh air. If breathing has stopped, apply artificial respiration. Get medical attention immediately.
- Skin**
  - Remove contaminated clothing and shoes. Wash the contaminated area of body with soap and fresh water. Get medical attention if symptoms occur. Wash clothing before reuse.
- Eye**
  - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. Get medical attention immediately if symptoms occur.
- Ingestion**
  - Call a physician or poison control center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

### Section 5 - Fire Fighting Measures

- Extinguishing Media**
  - LARGE FIRE: Water spray, fog or regular foam.
  - SMALL FIRES: Dry chemical, CO<sub>2</sub>, water spray or regular foam.
- Unsuitable Extinguishing Media**
  - Do not use direct stream of water.
- Firefighting Procedures**
  - Fight advanced or massive fires from safe distance or protected location. Avoid water in a straight hose stream as the stream will cause splatter and spread fire. If product is heated above its flash point, it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and are ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
- Unusual Fire and Explosion Hazards**
  - Combustible liquid. May release irritating or toxic gases, fumes, or vapors.
- Hazardous Combustion Products**
  - Carbon monoxide, carbon dioxide, hydrocarbons.
- Protection of Firefighters**
  - Firefighters should wear self-contained breathing apparatus and full protective gear.
- Flash Point**
  - 105°F(40°C) CC (Closed Cup)

## TRI-BUILT® 800 Tile Cement

<b>Explosion Limits</b>	
<b>Upper</b>	- 6 %
<b>Lower</b>	- 0.9 %
<b>Autoignition Temperature</b>	- 450°F(232°C)


### Section 6 - Accidental Release Measures

<b>Personal Precautions</b>	- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stay upwind. Ventilate the area before entry.
<b>Emergency Procedures</b>	- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up. Keep unauthorized personnel away.
<b>Environmental Precautions</b>	- Prevent spillage into waterways.
<b>Containment/Clean-up Measures</b>	- Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in suitable container. Use appropriate Personal Protective Equipment (PPE). Do not use water to flush spill area.
<b>Prohibited Materials</b>	- Avoid contact with strong oxidizing agents and acids.

### Section 7 - Handling and Storage

<b>Handling</b>	- <b>KEEP OUT OF THE REACH OF CHILDREN!</b> Keep away from heat and ignition sources – No Smoking. Use only with adequate ventilation.
<b>Storage</b>	- Keep container/package tightly closed and in a well-ventilated place. Do not store and transport with oxidizers, acids, etc. Store away from sources of ignition. Keep away from fire.
<b>Special Packaging Materials</b>	- No data available
<b>Incompatible Materials or Ignition Sources</b>	- Avoid contact with strong oxidizing agents and acids.

### Section 8 - Exposure Controls/Personal Protection

<b>Personal Protective Equipment</b>	
<b>Pictograms</b>	- 
<b>Respiratory</b>	- If listed exposure limits are expected to be exceeded, use approved respiratory protection suitable for the hazard. When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator.
<b>Eye/Face</b>	- Wear ANSI approved safety glasses with side shields or safety goggles.
<b>Hands</b>	- Wear chemical protective gloves made of Nitrile or Neoprene.
<b>Skin/Body</b>	- Wear clothing that covers the skin to prevent skin exposure.
<b>General Industrial Hygiene Considerations</b>	- Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling.
<b>Engineering Measures/Controls</b>	- Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

## TRI-BUILT® 800 Tile Cement

Exposure Limits/Guidelines					
	Result	Canada Ontario	NIOSH	OSHA	United States - California
1,2,4-Trimethylbenzene (95-63-6)	TWAs	Not established	25 ppm TWA; 125 mg/m3 TWA	Not established	Not established
Benzene, 1,3,5-trimethyl (108-67-8)	TWAs	Not established	25 ppm TWA; 125 mg/m3 TWA	Not established	Not established
Cellulose (9004-34-6)	TWAs	10 mg/m3 TWAEV (paper fibre, total dust)	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	10 mg/m3 PEL (total dust); 5 mg/m3 PEL (respirable fraction)
Kaolin (1332-58-7)	TWAs	2 mg/m3 TWAEV (containing no asbestos and less than 1% crystalline silica, respirable)	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	2 mg/m3 PEL (respirable dust, containing no asbestos fibers, < 1% crystalline silica)
Mineral Spirits (8052-41-3)	TWAs	525 mg/m3 TWAEV	350 mg/m3 TWA	500 ppm TWA; 2900 mg/m3 TWA	100 ppm PEL; 525 mg/m3 PEL
Asphalt (8052-42-4)	TWAs	0.5 mg/m3 TWAEV (fume, inhalable, as benzene-soluble aerosol)	Not established	Not established	5 mg/m3 PEL (fume)

### Exposure Control Notations

#### ACGIH

- Kaolin (1332-58-7):Carcinogens:A4 - Not Classifiable as a Human Carcinogen
- Asphalt (8052-42-4):Carcinogens:A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free)

## Section 9 - Physical and Chemical Properties

<b>Physical Form:</b>	Liquid(paste)	<b>Appearance/Description:</b>	Black paste.
<b>Color:</b>	Black	<b>Odor:</b>	Petroleum solvent odor.
<b>Odor Threshold:</b>	Not Available	<b>Boiling Point:</b>	300 to 400 F(148.8889 to 204.4444 C)
<b>Specific Gravity/Relative Density:</b>	= 1.093 Water=1	<b>Density:</b>	~ 9.10 lbs/gal
<b>Solvent Solubility:</b>	Yes	<b>Viscosity:</b>	Not Available
<b>Vapor Pressure:</b>	= 2 mmHg (torr) @ 68 F(20 C)	<b>Vapor Density:</b>	= 1 Air=1
<b>VOC (Vol.):</b>	< 250 g/L	<b>Volatiles (Wt.):</b>	Not relevant
<b>Volatiles (Vol.):</b>	Not Available	<b>Flash Point:</b>	105°F(40.5° C)
<b>Flash Point Test Type:</b>	CC (Closed Cup)	<b>UEL:</b>	6 %
<b>LEL:</b>	.9 %	<b>Heat of Combustion (ΔHc):</b>	Not relevant
<b>Autoignition:</b>	450 F(232.2222 C)	<b>Self-Accelerating Decomposition Temperature (SADT):</b>	Not relevant

## Section 10 - Stability and Reactivity

### Stability

### Hazardous Polymerization

### Conditions to Avoid

### Incompatible Materials

### Hazardous Decomposition Products

- Stable under normal temperatures and pressures.
- Hazardous polymerization not indicated.
- Avoid contact with strong oxidizing agents and flame.
- Strong oxidizers and acids.
- Carbon monoxide, carbon dioxide and hydrocarbons.

## TRI-BUILT® 800 Tile Cement

### Section 11 - Toxicological Information

Component Name	Concentration	CAS	Data
Water	2% TO 10%	7732-18-5	Acute Toxicity: ; orl-rat LD50:>90 mL/kg
Asphalt	40% TO 50%	8052-42-4	Acute Toxicity: ; ihl-hmn TDLo:10 mg/m3/5.5Y-I Tumorigen/Carcinogen: ; skn-mus TDLo:905 gm/kg/2Y-I
Kaolin	10% TO 20%	1332-58-7	Acute Toxicity: ; ihl-rat TLo:30 mg/m3/96W-I
Cellulose	2% TO 10%	9004-34-6	Acute Toxicity: ; ihl-rat LC50:>5800 mg/m3/4H
1,2,4-Trimethylbenzene	< 1%	95-63-6	Acute Toxicity: ; ihl-rat LC50:18000 mg/m3/4H

#### Other Information

- This product contains petroleum asphalt. Petroleum asphalt is not listed as a carcinogen by OSHA or NTP. The National Institute of Occupational Safety and Health (NIOSH), has concluded that at higher temperatures roofing asphalt fumes are a potential occupational carcinogen. If this product is heated or comes in contact with heated material, avoid breathing fumes. This product may contain small amounts of polycyclic aromatic hydrocarbons (PAH's) which are recognized carcinogens in humans and experimental animals. Mouse skin painting studies of roofing asphalt vapor concentrate have shown evidence of tumor formation associated with localized skin irritation in recent studies. Inhalation studies of high airborne concentrations of asphalt/bitumen fumes in rats and mice produced bronchitis, pneumonitis, and lung changes such as fibrosis and cell damage.

### Section 12 - Ecological Information

- Ecological Fate** - No data available.
- Persistence/Degradability** - No data available.
- Bioaccumulation Potential** - No data available.
- Mobility in Soil** - No data available.

### Section 13 - Disposal Considerations

- Product** - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

### Section 14 - Transportation Information

**DOT – Department of Transportation** - Not Regulated when shipped in containers <119 gallons.

**TDG - Canada Transportation of Dangerous Goods:** Tars, Liquids; UN1999; Hazard Class: 3; Packing Group: III

**TDG Transportation Other Information:** Not Restricted under General Exemption for small container packaging.

**IMO/IMDG –International Maritime Transport** - Tars, Liquids; UN1999; Hazard Class: 3; Packing Group: III

IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages.

**IATA - International Air Transport Association** - TARS, LIQUID; UN1999; Hazard Class: 3; Packing Group: III.

### Section 15 - Regulatory Information

- SARA Hazard Classifications** - Acute, Chronic
- Risk & Safety Phrases** - California PROP 65: Asphalt and Asphalt Fumes may contain detectable

## TRI-BUILT® 800 Tile Cement

amounts of chemicals known to the State of California to cause cancer or reproductive harm.

State Right To Know					
Component	CAS	MA	MN	NJ	PA
Water	7732-18-5	No	No	No	No
Asphalt	8052-42-4	Yes	Yes	Yes	Yes
mineral spirits	8052-41-3	Yes	Yes	Yes	Yes
Kaolin	1332-58-7	Yes	Yes	Yes	Yes
Cellulose	9004-34-6	Yes	Yes	Yes	Yes
1,2,4-Trimethylbenzene	95-63-6	Yes	Yes	Yes	Yes
Benzene, 1,3,5-trimethyl	108-67-8	Yes	No	No	No

Inventory			
Component	CAS	EU EINECS	TSCA
Water	7732-18-5	Yes	Yes
Asphalt	8052-42-4	Yes	Yes
mineral spirits	8052-41-3	Yes	Yes
Kaolin	1332-58-7	Yes	Yes
Cellulose	9004-34-6	Yes	Yes
1,2,4-Trimethylbenzene	95-63-6	Yes	Yes
Benzene, 1,3,5-trimethyl	108-67-8	Yes	Yes

### U.S. - CERCLA/SARA - Section 313 - Emission Reporting

- 1,2,4-Trimethylbenzene      95-63-6      < 1%      1.0 % de minimis concentration

## Section 16 - Other Information

**Last Revision Date** - 7/09/18

**Prepared By** - GG Inc.

### Disclaimer/Statement of Liability

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. Gardner Gibson or Beacon Sales Acquisition does not accept liability for any loss or damage that may occur from the use of this information.