

Material Name: PVC Cut-Edge Sealant Product #:307754

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name: PVC Cut-Edge Sealant

Synonym: Vinyl Sealant

Chemical Family: Solvent Based Sealant

Product Use: Sealant for PVC Single-Ply Roofing Membranes

Restrictions on Use: For industrial use only.

Manufacturer Information

Carlisle SynTec 1285 Ritner Highway Carlisle, PA 17013

USA

Phone: +1-800-479-6832

Emergency Phone #: +1-800-424-9300 (CHEMTREC)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Eye Irritant- Category 2A Specific Target Organ Toxicity - Single Exposure - Category 3 Flammable Liquids- Category 2

GHS Label Elements

The mixture is classified and labeled according to the Globally Harmonized System (GHS).

Symbol(s)





Signal Word

Danger

Hazard Statement(s)

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

Precautionary/ Response Statement(s)

Prevention / Response

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Page 1 of 10 Issue date: 2018-06-01 Revision 2.0



Product #:307754

Material Name: PVC Cut-Edge Sealant

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces.- No smoking

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground/bond container and receiving equipment.

P233 Keep container tightly closed.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position Comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/International regulations.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
109-99-9	Tetrahydrofuran	80-88
9002-86-2	Polyvinyl Chloride	9-11
28553-12-0	Diisononyl Phthalate	5.7
1843-05-6	(2-Hydroxy-4-(octyloxy)- phenyl)phenylmethanone	0.9-1
128-37-0	Butylated Hydroxytoluene	<0.2
75-01-4	Vinyl Chloride	<0.00001

Section 4 - FIRST AID MEASURES

EYES: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

SKIN: Generally the product does not irritate the skin.

INGESTION: Give large amounts of water. If symptoms persist, consult a doctor

INHALATION: If inhaled remove to fresh air. In case of complaints seek medical attention.

Page 2 of 10 Issue date: 2018-06-01 Revision 2.0



Product #:307754

Material Name: PVC Cut-Edge Sealant

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents:

Water with full jet.

Special hazards arising from the substance or mixture

No further relevant information available.

Advice for firefighters

Protective equipment:

No special measures required.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/surface or ground water.

Methods and material for containment or cleaning up:

Absorb with liquid-binding material (ie. Sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Page 3 of 10 Issue date: 2018-06-01 Revision 2.0



Material Name: PVC Cut-Edge Sealant Product #:307754

Section 7 - HANDLING AND STORAGE

HANDLING:

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

Information about protection against explosions and fire:

Keep ignition sources away – Do not smoke. Protect from heat. Protect against electrostatic charges.

STORAGE

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Specific end use(s) No further relevant information available.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

tetrahydrofuran	109-99-9		
PEL:	Long-term value 200 ppm ;590 mg/m ³		
REL	Short-term value 250 ppm ;735 mg/m³ Long-term value 200 ppm ;590		
TLV	Short-term value 100 ppm ;295 mg/m ³	Long-term value Skin 200 ppm ;147 mg/m ³	
BEI	2 mg/L; urine, end of shift, tetrahydrofuran		
Vinyl Chloride	75-01-4		
TWA	1ppm -ACGIH		
TWA	1ppm – OSHA		
STEL	5ppm – OSHA		

Page 4 of 10 Issue date: 2018-06-01 Revision 2.0



Material Name: PVC Cut-Edge Sealant Product #:307754

Individual Protection Measures, such as Personal Protective Equipment General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Eye/face protection

Tightly sealed goggles.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Select the glove material based on penetration times, rates of diffusion and degradation.

Additional Information: The lists that were valid during the creation were used as basis. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Respiratory Protection

Not required.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid	Physical State	liquid
Odor	Ether-like	Color	Colorless
Boiling Point Range	65 °C (149 °F)	Flammability Limit	N/A
Autoignition	Not determined	Flash Point	-21 °C (-6 °F)
Danger of explosion	May form expolsive peroxides	Explosion limits	1.5 vol% Low 12 vol% Upper
Vapor pressure @ 20 °C (68 °F)	200 hPa (150 mm Hg)	Relative density	Not determined
Vapor Density (air=1)	Not determined	voc	780 g/l
Solubility in/ Miscibility with water	Not miscible or difficult to mix	Partition coefficient (noctanol/water)	Not determined
Dynamic/Kinematic	Not determined	Organic Solvents	83.8%

Page 5 of 10 Issue date: 2018-06-01 Revision 2.0



Material Name: PVC Cut-Edge Sealant Product #:307754

Density @ 20 °C (68 oF)	0.930 g/cm3 (7.76 lbs/gal)	pH-value	7
Melting Point Range	-108 °C (-163 °F)	Ignition Temperature	230 °C (446 °F)

COMMENTS: 5.27 lb VHAP/lb Solid 84.1% by weight HAP

Section 10 - STABILITY AND REACTIVITY

Reactivity

No further relevant information available.

Chemical stability

Thermal decomposition/conditions to be avoided:

No decomposition if used according to specifications

Possibility of hazardous reactions

No dangerous reactions known.

Conditions to avoid

No further relevant information available.

Incompatible materials:

No further relevant information available.

Hazardous decomposition products:

No dangerous decomposition products known.

Section 11 - TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

109-99-9 tetrahydrofuran

Oral LD50 2500 mg/kg (rat)

75-01-4 Vinyl Chloride

Oral LD50 500mg/kg (rat)

Inhalation LC50 18lb/h (rat) (15 min)

Primary irritant effect:

On the skin:

No irritant effect.

On the eye:

Irritating effect.

Sensitization:

No sensitizing effects known.

Additional toxicological information:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

9002-86-2 polyvinyl chloride

75-01-4 vinyl chloride

Page 6 of 10 Issue date: 2018-06-01 Revision 2.0



Material Name: PVC Cut-Edge Sealant

NTP (National Toxicology Program)

Known human carcinogen.

OSHA hazard communication carcinogen list

On list.

OSHA specifically regulated carcinogen list

On list.

Section 12 - ECOLOGICAL INFORMATION

Toxicity

28553-12-0 diisononyl phthalate

LC50 420 ug/l fresh water (channel catfish) 96 h

LC50 4670 ug/l fresh water (redear sunfish) 96 h

LC50 0.140 ug/l fresh water (bluegill) 96 h

EC50 0.060 mg/l fresh water (aquatic invertebrates, water flea) 48 h

EC50 1800 mg/l fresh water (aquatic plants, green algae) 96 h

NOEC 34 ug/l fresh water (aquatic invertebrates, water flea) 21 d

NOEC 0.034 mg/l fresh water (aquatic invertebrates, water flea) 21 d

75-01-4 vinyl chloride

LC50 210 mg/l (Brachydanio rerio, fish) 96 h

Aquatic toxicity

No further relevant information available.

Persistence and degradability

No further relevant information available.

Bioaccumulative potential

28553-12-0 diisononyl phthalate: LogPow: 8.8-9.7, BCF: 3.00, Potential: Low 75-01-4 vinyl chloride: LogPow: 1.58, BCF Fish: no significant bioaccumulation

Mobility in soil

No furtherrelevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

PBT: Not applicable. **vPvB:** Not applicable.

Other adverse effects No futher relevant information available.

Section 13 - DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation:

Page 7 of 10 Issue date: 2018-06-01 Revision 2.0

Product #:307754



Material Name: PVC Cut-Edge Sealant Product #:307754

Disposal must be made according to official regulations.

Section 14 - TRANSPORT INFORMATION

UN-Number

DOT, ADR, IMDG, IATA UN1133

UN proper shipping name

DOT Adhesives, containing a flammable liquid.

ADR Not determined

IMDG, IATA Not determined

Transport hazard class(es)

DOT

Class 3 Flammable liquids.

Label 3

ADR Not determined

Class Not determined

IMDG< IATA Not determined

Class Not determined

Label Not determined

Packing group

DOT, ADR, IMDG, IATA II

Environmental hazards:

Marine pollutant: No

Special precautions for user Warning: Flammable liquids

Danger code (Kemler) 33 EMS Number: Not applicable.

Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC Code Not applicable.

Transport/Additional information:

DOT

Remarks: ERG Guide Number: 128

UN "Model Regulation": UN1133, Adhesives, 3, II

Section 15 - REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Sara

Section 355 (extremely hazardous substances):

Mixture substances are not listed.

Section 313 (Specific toxic chemical listings):

Mixture substances are not listed.

TSCA (Toxic Substance Control Act):

109-99-9 tetrahydrofuran is listed.

Proposition 65

Chemicals known to cause cancer:

Page 8 of 10 Issue date: 2018-06-01 Revision 2.0



Product #:307754

Material Name: PVC Cut-Edge Sealant

28553-12-0 diisononyl Phthalate

75-01-4 vinyl chloride

Chemicals known to cause reproductive toxicity for females:

Mixture substances are not listed'

Chemicals known to cause reproductive harm to males:

Mixture substances are not listed.

Chemicals known to cause developmental toxicity:

Mixture substances are not listed.

TLV (The shold Limit Value established by ACGIH)

109-99-9 tetrahydrofuran

NIOSH-Ca (National Institute for Occupational Safety and Health)

Mixture substances are not listed

National regulations

Mixture substances are not listed.

State Right to Know

Mixture substances are not listed.

Chemical safety assessment: A chemical Safety Assessment has not been carried out.

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 1 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 1 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Other Information

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of the need that the information is current, applicable, and suitable to their circumstances.

Summary of Changes

Revision Date: June 1, 2018 Revision Note: General Update

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO -

Page 9 of 10 Issue date: 2018-06-01 Revision 2.0



Material Name: PVC Cut-Edge Sealant

Product #:307754

International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIstsTM - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.

Page 10 of 10 Issue date: 2018-06-01 Revision 2.0